



**邀請報價**

供應商:致各競投者	傳真號碼:	電話號碼:
採購申請編號:119614	日期:30/10/2018	頁數:1+6

煩請 貴商號就下列貨品或服務提供報價，並請 貴商號根據以下要求於指定時間前將有關報價資料送交本大學為荷。逾時遞交報價者，本大學恕不接受。

限期：**2018年11月5日17時30分或之前**

**1. 貨物或服務內容：**

項目	內容	數量	價目
1	為澳門大學教與學優化中心（E6-3122等）供應資訊設備、影音設備及配件  *詳情請參考附件（共六頁）。	1.0	
****請於報價單上簽署及蓋上有效的競投商號／公司印章。			

\* 如 貴商號為區域總代理商／總程式及軟件開發商／總維修站等，或已取得ISO9000或ISO14000認證，須提交相關証明文件或聲明書以作評選之用。

\*\* 歡迎提供相關環保產品，以供選擇。

**2. 送交報價單形式：**

☒ 傳真No.：28831103／電郵方式：[EllaSou@umac.mo](mailto:EllaSou@umac.mo)；

☒ 報價單直接送交至澳門大學，N6 行政樓，4012 室採購處。在信封面上請註明〔報價單〕字樣及〔採購申請編號〕並封口蓋上公司印章。

**3. 報價條件：**

☒ 交貨日期； ☐ 遞交樣本； ☒ 保養日期； ☐ 完工日期； ☒ 付款方式；

☒ 報價單條款及有效日期； ☐ 附同 (M1) 及 (M8) 營業稅單副本；

如蒙垂詢，請聯絡蘇小姐（電話：+853 8822 8568 及電子郵件：[EllaSou@umac.mo](mailto:EllaSou@umac.mo)）



採購處處長

**備註：**

競投者在投標前有責任閱讀刊登於大學網頁的 "競投者注意事項"

([https://pct.admo.umac.mo/for-suppliers/attention-to-all-bidders\\_ch/](https://pct.admo.umac.mo/for-suppliers/attention-to-all-bidders_ch/))。倘有需要，競投者可聯絡大學採購負責人員索取有關資料。

Item No.	Item	Location	Specifications / Description	Minimum requirements:	Reference Brand and Model	Quantity	Unit Price (MOP)	Total Price (MOP)
1	Audio recorder / USB interface	E6-3122	high-resolution audio recorder with integrated USB audio streaming, sound recording Kashmir Microphone Preamps, USB Audio-Recording Interface, Built-In 1/4"-20 Mount for Videographers, Inputs: Inputs, Mic: 3 XLR active-balanced; 4k input Z, 1 Line: XLR active-balanced; 4k input Z, 1 Aux/Mic in: 3.5mm TRS, 2-channel unbalanced; 100k input Z; USB Audio Interface (USB-C); 5-in/2-out; 44.1 to 96 kHz; 16/24-bit; and Class-compliant USB 2.0 high speed, Limiter at all gain stages, range > 40dB. First stage analog, subsequent stages digital	sound recording Kashmir Microphone Preamps Inputs, Mic: 3 XLR active-balanced; 1 Aux/Mic in: 3.5mm TRS; USB Audio Interface (USB-C)	Sound Devices Mix-Pre-3	1		
2	Backdrop stand	E6-3122	Backdrop stand kit for paper (Qty. 1) - Kit includes: 2 x L-B2900GH stands; 290 cm tall, 1 x cross beam; collapsed 108 cm wide, expanded 275 cm wide, 6 x CBH-5 bracket, 3 x B-reel roll holder, 3 x Chain (1.7 m), 3 x Weight for chain No background rolls included		Falcon Eyes Background System SPK-1A for 3 Rolls	3		
3	Backdrop stands for blankets	E6-3122	Light stand, Max Height: 96", 5/8" Stud with 1/4"-20 Threaded Top		Impact Air-Cushioned Light Stand (Black, 8)	8		
4	Camera body	E6-3122	Camera body, 26MP CMOS full-frame sensor with Dual Pixel AF, 1080/60p video capture with in-lens + digital stabilization, 45-point all-cross-type AF system, Dual Pixel AF for both stills and video capture	26MP CMOS full-frame sensor with Dual Pixel AF, 1080/60p video capture with in-lens + digital stabilization, 45-point all-cross-type AF system,	Canon EOS 6D Mark II	1		
5	Camera lens	E6-3122	EF-Mount Lens 24-1-55mm Full-Frame Format Aperture Range: f/4 to f/22		Canon EF 24-105mm f/4L IS USM Lens	1		
6	Headphones	E6-3122	Studio headphones; monitor headphones are tuned flat for incredibly accurate audio monitoring across an extended frequency range, detachable cable, Driver Diameter 40 mm, Frequency Response 15 - 24,000 Hz, Sensitivity 98 dB, Impedance 35 ohms	detachable cable from headphones Driver Diameter 40 mm, Frequency Response 15 - 24,000 Hz, Sensitivity 98 dB, Impedance 35 ohms	Audio-Technica ATH-M40x	3		
7	LED lighting panels	E6-3122	Round LED Light Kit, soft lighting for all applications, includes 3x 48TD Soft LED Lights, 3x Light Stands Max 2.5m, 3x FENTION FS-BP95 Series Small Size V-LOCK Li-Ion Batteries, 1x FARSEEING Portable AC/DC Charger (530334)		Falcon Eyes Ultra Thin Soft Edge light bulble kit, SO-48TD Triple LED Kit 3 (PK0358)	1		
8	Light stands	E6-3122	Folded height (approx.): 36 inches/92 centimeters Maximum height (approx.): 79 inches/200 centimeters Max. load capacity (approx.): 17.5 pounds/ 8 kilograms Spigot: 1/4 inch (need adapter to convert to 3/8 inch) Tube Diameter: 25-22-19 mm		Neewer Photography Light Stand	4		
9	Microphone - indoor dialogue	E6-3122	Broadcast quality hypercardioid Condenser Microphone for indoor dialogue with one speaker, internal transformerless circuitry to reduce distortion, Frequency Range 20 Hz to 20 kHz, Signal to Noise Ratio 78 dB 1 kHz at 1 Pa, Equivalent Noise Level 16 dB.	hypercardioid Condenser Microphone Frequency Range 20 Hz to 20 kHz, Signal to Noise Ratio 78 dB 1 kHz at 1 Pa, Equivalent Noise Level 16 dB.	Audio-Technica AT4053b	1		
10	Microphone - indoor dialogue	E6-3122	Broadcast quality condenser Microphone for indoor dialogue with one speaker, internal transformerless circuitry to reduce distortion, Frequency Range 20 Hz to 20 kHz, Signal to Noise Ratio 78 dB 1 kHz at 1 Pa, Equivalent Noise Level 16 dB.	condenser Microphone Frequency Range 20 Hz to 20 kHz, Signal to Noise Ratio 78 dB 1 kHz at 1 Pa	Audio-Technica AT4051b Cardioid Condenser Microphone for indoor dialogue with several speakers	1		



Specification of PR#119614

Item No.	Item	Location	Specifications / Description	Minimum requirements:	Reference Brand and Model	Quantity	Unit Price (MOP)	Total Price (MOP)
11	Microphone - indoor voice recordings	E6-3122	USB Broadcast Microphone, Broadcast Sound Quality, 28mm dynamic capsule, 18-bit resolution, 8-48kHz sampling, Windows and Mac compatible	USB Broadcast Microphone 28mm dynamic capsule, 18-bit resolution, 8-48kHz sampling	USB Broadcast Microphone - Rode Podcaster	2		
12	Microphone - moving subjects	E6-3122	Two Person Lavalier Interviewer Kit for iOS Devices, 2x Rode smartLav+ Lavalier Mics, SC6 Dual TRRS Input Adapter, HPC-A30 Closed-Back Monitor Headphones	2x Rode smartLav+ Lavalier Mics, SC6 Dual TRRS Input Adapter	Rode smartLav+ Two Person Lavalier Interviewer Kit for iOS Devices	1		
13	Power conditioner	E6-3122	Power conditioner to reduce noise from AC supply and surge protector, AC Current Capacity: 10 Amp capacity required, Output: 10 Amp RMS (both outlets combined) AC Noise Attenuation, Transverse (Differential) Mode >40dB @ 100kHz, >50dB @ 500kHz, (linear attenuation curve from 0.05 to 100 ohms line impedance), Transient Voltage Surge Suppression 230VAC - Series Multi-Stage Protection, Non-Sacrificial with Zero Ground Contamination	Min Output: 10 Amp RMS AC Noise Attenuation, Transverse (Differential) Mode >40dB @ 100kHz, >50dB @ 500kHz	Furman AC-210A E	3		
14	Stand	E6-3122	Tripod Microphone Stand with Telescoping Boom, Height 91.9 to 160 cm, Boom Arm Telescopes from 19.3 to 33.9.		Auray MS-5230T Tripod Microphone Stand with Telescoping Boom	3		
15	Stand	E6-3122	Tabletop microphone stand with microphone clip, adjustable height from 11-16 inches		Hamilton Stands KB810M Nu-Era Tabletop Mic Stand with Bag and Mic Clip	3		
16	Stand	E6-3122	The stand supports all Planar monitors between 15" - 27" with maximum weight of 17.64 lbs. NUC, and Chromebox can be mounted on the rear of the stand via clamps or VESA mounting plate. Supports displays between 15"- 27" with maximum weight of 17.64 lb Flexibility to tilt up and down +25° and -5°, Rotates monitor 360° for landscape or portrait mode. Swivels 360°. Height adjustable up to 5" (130mm). Supports PCs (Max: 13.39" x 13.39" x 3.94", Min: 6.89" x 6.89" x 2.35"), weight limit of 22.1 lbs		Planar Universal All-In-One Height Adjust Stand, Part Number: 997-7938-00	2		
17	Teleprompter	E6-3122	iPad Smartphone Teleprompter, fits all iPads Pro or any Smartphone, Collapsible, No Assembly Required, Tripod Mount Ready, 70/30 Beamsplitter Glass		Glide Gear iPad Smartphone Teleprompter	1		
18	Tripod	E6-3122	Video Tripod with variable fluid drag system in both pan and tilt movements. Video Head with Flat Base: Fixed counterbalance system, Load Capacity, Static: 7.0 kg, Counterbalance supports 4 kg, Head to Tripod Mounting Thread 3/8"-16 thread, Counter Balance System Spring-loaded, Counter Balance Range One fixed spring for 4 kg camera weight, Quick Release/Wedge Plate 504PLONG plate with 1/4"-20 screw and 1/4"-20 to 3/8"-16 adapter, Balance Plate 504PLONG plate slides 83.0 mm, Tilt Drag Continuously adjustable from 0 to max level, Tilt Range -80° to +90° tilt range front to back, Spring Loaded Counter Balance Yes, Pan Drag Continuously adjustable from 0 to max level. Aluminum Tripod: Load Capacity 9 kg, Maximum Working Height 169.9 cm, Folded, Length 61 cm, Head Mount Type 3/8"-16 Screw, Weight 2.5 kg, Materials Aluminum Alloy, Leg Sections 3.		Manfrotto MT055XPRO3 Aluminum Tripod with 502HD Fluid Head Hybrid Video Kit	1		
19	Camera tripod	E6-3111	Compact stand for flexible video and photo shooting with 2 leg angles Pan and tilt movement with fluid drag system Max load 4KG, Min height 43 cm, Max height 151		Manfrotto Befree live fluid head with Befree aluminum tripod system	1		

Specification of PR#119614

Item No.	Item	Location	Specifications / Description	Minimum requirements:	Reference Brand and Model	Quantity	Unit Price (MOP)	Total Price (MOP)
20	Monitor - 24" Touchscreen	E6-3122	Use with Mini-PC (HDMI): Display Size (in.):22 Viewable Area (in.):21.5 Panel Type:IPS Resolution:1920 x 1080 Static Contrast Ratio:1,000:1 Dynamic Contrast Ratio:50,000,000:1 Light Source: LED Brightness:250 cd/m2	Use with Mini-PC (HDMI): Display Size (in.):22 Viewable Area (in.):21.5 Panel Type:IPS Resolution:1920 x 1080 Static Contrast Ratio:1,000:1 Dynamic Contrast Ratio:50,000,000:1	ViewSonic TD2230	1		
21	Monitor - 24" Touchscreen	E6-3122	Use with MacBook 1 / Mini-PC (USB_C) Display Size: 21.5-inch (diagonal) 4K display with IPS technology Resolution: 4096-by-2304 with support for millions of colors Brightness: 500 cd/m² Color Gamut: P3 wide color gamut Ports: One USB-C (input), three USB-C (USB 2, 480 Mbps)	Resolution: 4096-by-2304 with support for millions of colors Brightness: 500 cd/m² Color Gamut: P3 wide color gamut Ports: One USB-C (input), three USB-C (USB 2, 480 Mbps)	22" Class UltraFine™ 4K IPS LED Monitor	1		
22	Monitor - 27"	E6-3122	Use with iMac: 4K monitor LED-backlit LCD monitor - 27", External monitor for video editing, Native resolution 4K UHD (2160p) 3840 x 2160 (DisplayPort: 60 Hz, HDMI: 30 Hz), stand enables tilt (5° forward or 21° backward), pivot, swivel, stand enables tilt (5° forward or 21° backward), pivot, swivel, Brightness 350 cd/m², Contrast Ratio 1000:1 / 2000000:1 (dynamic), Response Time 9 ms (gray-to-gray), Color Support 1.07 billion colors Support 1.07 billion colors Input Connectors HDMI, DisplayPort, Mini DisplayPort, MHL; Dimensions (WxDxH) - with stand 25.2 in x 8 in x 16.7 in	Native resolution 4K UHD (2160p) 3840 x 2160 (DisplayPort: 60 Hz, HDMI: 30 Hz), stand enables tilt (5° forward or 21° backward), pivot, swivel, Brightness 350 cd/m², Contrast Ratio 1000:1 / 2000000:1 (dynamic), Response Time 9 ms (gray-to-gray), Color Support 1.07 billion colors Input Connectors HDMI, DisplayPort, Mini DisplayPort, MHL; Dimensions (WxDxH) - with stand 25.2 in x 8 in x 16.7 in	Dell P2715Q	1		
23	Monitor - 27"	E6-3122	Use with MacBook Pro (2016 and later): Thunderbolt 3 / USB Type-C Inputs 5K (5120 x 2880) IPS Display, 1200:1 Static Contrast Ratio, 500 cd/m² Brightness, 178°/178° Viewing Angles, 14 ms (GIG) Response Time, 10-Bit, 1.07 Billion Colors Compatibility: 5120 x 2880 MacBook Pro (2016 and later)	Thunderbolt 3 / USB Type-C Inputs 5K (5120 x 2880) IPS Display, 1200:1 Static Contrast Ratio, 500 cd/m² Brightness, 178°/178° Viewing Angles, 14 ms (GIG) Response Time, 10-Bit, 1.07 Billion Colors Compatibility: 5120 x 2880 MacBook Pro (2016 and later)	LG UltraFine 5K Display LG 27MD5KB-B	1		
24	Monitor - 27"	E6-3122	Use with Mini PC 2 or iMac: 4K UHD resolution (3840 x 2160) 27 Inch IPS Display HDR10 compatible USB Type-C Connectivity AMD FreeSync Technology sRGB 99% Color Gamut	4K UHD resolution (3840 x 2160) 27 Inch IPS Display HDR10 compatible USB Type-C Connectivity AMD FreeSync Technology sRGB 99% Color Gamut	LG 27UK850-W 27" 4K UHD IPS Monitor	1		
25	Web-camera	E6-3122	4K UHD video calling at 30 fps, HD 1080p at 60 fps, 5X zoom, compatible with macOS 10 or higher	4K UHD video calling at 30 fps, HD 1080p at 60 fps, 5X zoom	Logitech 4k Pro Webcam	1		
26	Adaptor	E6-3122	Mini-DisplayPort Male to DisplayPort Male Cable 150 cm			2		
27	Adaptor	E6-3122	Mini-DisplayPort Male to Mini DisplayPort Male Cable 150 cm			1		
28	Adaptor	E6-3122	USB 3.1 Type C (male) to DisplayPort Adapter (Female)		VisionTek USB 3.1 Type C to DisplayPort Adapter (M/F)	1		
29	Adaptor	E6-3122	Lightning connector to 3.5 mm Headphone Jack Adapter		Lightning to 3.5 mm Headphone Jack Adapter	2		
30	SD Card	E6-3122	64GB Storage Capacity, UHS-I / V30 / Class 10, Max Read Speed: 95 MB/s, Max Write Speed: 90 MB/s, Min Write Speed: 30 MB/s		SanDisk 64GB Extreme PRO SDXC UHS-I Memory Card	6		





Item No.	Item	Location	Specifications / Description	Minimum requirements:	Reference Brand and Model	Quantity	Unit Price (MOP)	Total Price (MOP)
31	Wireless keyboard	E6-3122	Replacement keyboard for iMac: Compatible with Mac with OS X 10.6.8 or later and Apple TV 5.2 or later Bluetooth connectivity Dimensions: 10.9 x 4.9 x 0.6 in		Logitech Keyboard K380	5		
32	Wireless keyboard	E6-3113 / E6-3114	Replacement keyboard for PC: Built-in Multi-Touch Touchpad with Unifying Receiver 2.4GHz wireless connection 10m reliable wireless range Unifying receiver USB range extender		Logitech Keyboard K900 plus	2		
33	Wireless mouse	E6-3122 / E6-3113 / E6-3114	Replacement mouse for video editing on iMac/PC: Rechargeable Battery Unifying receiver or Bluetooth Smart wireless technology Compatible with macOS and Windows OS 1000-DPI precision sensor 7 Programmable buttons , scroll wheel and thumb wheel		Logitech MX Master 2S	5		
34	Wireless touchpad	E6-3122 / E6-3113 / E6-3114	Upgrade for video editing on iMac Bluetooth 4.0-enabled Gestures: Scroll, Click, Swipe, Rotate Dimensions: 6.3 x 4.52 x 0.43" Range: 33 feet		Apple Magic Trackpad 2	5		
35	Wireless AP	E3-G033 / E6-2115 / E6-2116	For network connect AC1900 ultimate AC performance : 600+1300 Mbps Data Rate: 802.11n : up to 450 Mbps; 802.11n TurboQAM : up to 600 Mbps; 802.11ac : up to 1300 Mbps Operating Frequency: 2.4 GHz / 5 GHz Antenna: External antenna x 3, MIMO technology, 2.4 GHz 3 x 3, 5 GHz-1 3 x 3 Memory: 128 MB Flash, 256 MB RAM	AC1900 ultimate AC performance : 600+1300 Mbps Data Rate: 802.11n : up to 450 Mbps; 802.11n TurboQAM : up to 600 Mbps; 802.11ac : up to 1300 Mbps Operating Frequency: 2.4 GHz / 5 GHz Antenna: External antenna x 3, MIMO technology, 2.4 GHz 3 x 3, 5 GHz-1 3 x 3 Memory: 128 MB Flash, 256 MB RAM	ASUS RT-AC68U (AC1900)	3		
36	Wireless presentation box	E3-G033 / E3-G034 / E3-1032 / E6-2115 / E6-2116	Output: 2160p with Dolby Vision and HDR10 Processor: A10X Fusion chip with 64-bit architecture Ports: HDMI 2.0a, Gigabit Ethernet, IR Receiver	Output: 2160p with Dolby Vision and HDR10 Processor: A10X Fusion chip with 64-bit architecture Ports: HDMI 2.0a, Gigabit Ethernet, IR Receiver	Apple TV 4K 32GB	7		
37	Wireless presenter	E6-3112	Controls PowerPoint and PC Gesture controls Connection Type: Bluetooth and 2.4GHz wireless connection Sensor: 3D accelerometer and Gyroscope Sensor technology: Motion sensor	Sensor: 3D accelerometer and Gyroscope Sensor technology: Motion sensor	Logitech Spotlight Presentation Remote	1		
38	Auphonic license	E6-3122	Auphonic web service: automatic audio post production, loudness, leveling, audio restoration, etc.		One-Time Credits 25 hours (account needed, e.g. ctle@umac.mo)	1		
39	Audio recorder accessories	E6-3122	Spare battery sled for the Sound Devices MixPre-3		MX-4AA Battery Sled	1		
40	Audio recorder camera mount	E6-3122	Universal Adjustable Camera Cage: Plenty of 1/4"-20 & 3/8"-16 Threaded Holes, Extendible Side Support Comes with Two Kinds of Sliding Bar, Fits Camera Height: 68mm to 105mm/105mm to 145mm, Canon 70D.		CAMVATE Universal Adjustable Camera Cage	1		
41	Cable	E6-3122	XLR cable, XLR M to XLR F, for studio & broadcast, 98% Braided Shield, 3 meters, 24-Gauge OFC Conductors		Kopul Studio Elite 4000 Series XLR M to XLR F Microphone Cable - 10' (3.0 m), Black	2		
42	Cable	E6-3122	3.5mm TRS Patch Cable, male to male TRS connectors, Gold-Plated 3.5mm Mini-Connectors, Right-Angle Plugs Fit into Tight Spaces, Coiled Design Reduces Clutter, OFC Spiral Shielding Reduces RFI		Pearstone CRSM-830 Coiled Right-Angle Stereo Mini Cable (8-30")	2		

Item No.	Item	Location	Specifications / Description	Minimum requirements:	Reference Brand and Model	Quantity	Unit Price (MOP)	Total Price (MOP)
43	Cable	E6-3122	Thunderbolt 3 (USB-C) cables .8 m		Thunderbolt 3 (USB-C) cables	2		
44	Camera battery	E6-3122	Compatible with Canon 6D Mark II, Amp-Hours 1865.00 mAh, Chemistry: lithium-ion, Output Voltage 7.2 VDC, Dimensions (W x H x D) 2.2 x 0.8 x 1.5" / 5.6 x 2.0 x 3.8 cm		Canon LP-E6N Lithium-Ion Battery Pack (7.2V, 1865mAh)	1		
45	Clips	E6-3122	Photography heavy duty muslim clamps, (6)x Photography heavy duty muslim clamps. Maximum opening 2 inch mouth, dimensions 4.5 inches long, rugged, pivoting pads. Material: Nylon		Emart Heavy Duty Muslim Spring Clamps, 4.5 inch Photo Booth Backdrop Clips for Photography Studio - 6 Pack	2		
46	Microphone accessories	E6-3122	Shock mount for AT4053b mic. Accepts cylindrical and tapered microphones. Features a constant-tension clutch and 360° rotation. Compatible with 3/8"-16 and 5/8"-27 threaded stands		Microphone Shock Mount AT8415	1		
47	Microphone accessories	E6-3122	Shock mount for AT4051b mic. Secure spring-clip fits cylindrical microphones. Permits easy microphone insertion and removal without detaching mic cable		Microphone Shock Mount AT8410a	1		
48	Microphone accessories	E6-3122	Windscreens for AT4053b and AT4051b mics		Windscreens AT8159	2		
49	Microphone accessories	E6-3122	Windshield for Rode Podcaster microphone		Windshield - Rode WS2	2		
50	Microphone accessories	E6-3122	Microphone shock mount (Qty. 1). Provides isolation from external vibrations. Dimensions: 122.00mmH x 110.00mmW x 155.00mmD. Compatible with Rode PSM1		Microphone shock mount - Rode PSM1	2		
51	Microphone accessories	E6-3122	Premium shielded extension cable for the smartLav and smartLav+ TRRS microphones, 6 meters		Rode SC1 TRRS Extension Cable For SmartLav Microphone - 20'	2		
52	Microphone accessories	E6-3122	3.5mm TRRS to TRS Adapter, a high-quality shielded adaptor, designed to allow the smartLav to connect to 3.5mm TRS devices such as cameras and audio recorders		Rode SC3 3.5mm TRRS to TRS Adapter for smartLav	2		
53	Power strip	E6-3122	Power strip with one IEC C14 plug and four Type-G output plugs			6		
54	Sound Absorption Blankets	E6-3122	Sound Blankets for focusing absorbing noise, soundproofing vocal booths and acoustic room treatment. One side is black, the other is white - to brighten or lighten a room or for special lighting conditions. Filled with sound absorptive recycled cotton fibers and the outer material made from cotton-mix fabric, washable		VB-70G (6) Sound Blankets Producers Choice- White-Black. Set of 6, Size (80"x80") with Grommets	1		
55	Video Conferencing System	E6-3111	Rally Plus Video Conferencing System: 4K PTZ (pan-tilt-zoom) camera with RightSense technology Conference room system, supports: 4K, 1440p, 1080p at 30fps 1080p at 30fps and 60 fps; Smooth motorized pan, tilt and zoom Pan: ±90°, Tilt: +50° / -90°, 15x HD zoom 90° field of view, Standard tripod thread table and display hub, two speakers and two mic pods	Rally camera only: 4K PTZ (pan-tilt-zoom) camera with RightSense technology	Logitech Rally Plus	1		
56	Laptop	E6-3122	For video production Processor, i7-8850H, GPU Radeon Pro 560X RAM 32GB 2400MHz, Storage 1TB SSD Four Thunderbolt 3 ports	Processor: i7-8850H, GPU Radeon Pro 560X RAM 32GB 2400MHz, Storage 1TB SSD Four Thunderbolt 3 ports	Apple MacBook Pro "Core i7" 2.6 15" Touch/Mid-2018 MR942LL	2		
57	Laptop	E3-G033 / E6-2115 / E6-3112	Laptops for training workshops for academic staff 8th Generation Intel® Core™ i7-8750H Processor 16GB LPDDR3 1866MHz 512GB Solid State Drive 15-in. display	8th Generation Intel® Core™ i7-8750H Processor 16GB LPDDR3 1866MHz 512GB Solid State Drive 15-in. display	Dell XPS 15 Touch 9570, RAM 16GB, 512GB M.2	8		



Specification of PR#119614

Item No.	Item	Location	Specifications / Description	Minimum requirements:	Reference Brand and Model	Quantity	Unit Price (MOP)	Total Price (MOP)
58	PC kit	E6-3122	Core i7-8809G, 8M Cache, up to 4.20 GHz Radeon™ RX Vega M GH graphics Mini-PC for Video Recording & Editing AMD Radeon RX Vega M GPU • Full-size SDXC card slot • Dual HDMI 2.0 supporting 4K @ 60Hz • Dual mDP 1.2 (up to 3 displays each) • Dual Thunderbolt 3 (supports Alt-DP)	Core i7-8809G, 8M Cache, up to 4.20 GHz Radeon™ RX Vega M GH graphics	Intel NUC8i7HYK	1		
59	PC kit	E6-3122	Mini-PC storage drive 1&2 Storage type m.2 - M.2 2280 - 512GB - PCIe Gen3, X4, NVMe 1.3	M.2 2280 512GB PCIe Gen3, X4, NVMe 1.3	Samsung 970 PRO 512GB - NVMe PCIe M.2 2280 SSD (MZ-V7P512BW)	2		
60	PC kit	E6-3122	Mini-PC RAM memory 16GB 2666MHz DDR4 CL15 260-Pin	Mini-PC RAM memory 16GB 2666MHz DDR4 CL15 260-Pin	Kingston Technology HyperX Impact 16GB 2666MHz DDR4 CL15 260-Pin HX426S15IB2	1		
61	PC Kit	E3-3034 / E3-3041	CPU: Intel i3-8121U processor Graphics: Radeon 540, 2GB GDDR5 Mini-PC for upgrading SMARTBoards	CPU: Intel i3-8121U processor Graphics: Radeon 540, 2GB GDDR5	Intel NUC8i3 CYSM	2		
62	PC Kit	E3-3034 / E3-3041	INTEL 512GB 760p 2280, 3230 / 1625 MB/s, 3D TLC, PCIe 3.0 x4 NVMe, M.2 SSD Mini-PC storage drive 1 SSD storage m.2	INTEL 512GB 760p 2280, 3230 / 1625 MB/s, 3D NAND TLC, PCIe 3.0 x4 NVMe, M.2 SSD	INTEL® SSD 760P SERIES (512GB, M.2 80mm, PCIe® 3.0 x4, 3D2, TLC)	2		
63	Desk cart	E6-3112	Mobile Desk Cart for Laptop: Pneumatic Height Adjustment - Raise and lower the desk from 27.1 to 41.9 inches with the lever-operated air-powered cylinder Large Size Tabletop - Desk top measures 28.1 inches wide by 19.6 inches deep Rolling Mobile Workstation - Four 2.4-inch casters; 2 locking		Seville Classics AIRLIFT XL Pneumatic Sit-Stand Mobile Desk Cart, Height-Adjustable from 27.1 to 41.9, Espresso Link: <a href="http://a.co/asx4XWP">http://a.co/asx4XWP</a>	2		
64	Hub	E6-3122	USB-C Hub Ports: Gigabit Ethernet, 3 USB 3.0 ports and micro/SD card, HDMI Connects 4K HDMI or DisplayPort monitor Charging capabilities with USB-C PD standard, capable of multi-directional power flow (up to 49W)	Ports: Gigabit Ethernet, 3 USB 3.0 ports and micro/SD card, HDMI Connects 4K HDMI or DisplayPort monitor Charging capabilities with USB-C PD standard, capable of multi-directional power flow (up to 49W)	Satechi TYPE-C MULTI-PORT ADAPTER 4K WITH ETHERNET V2	3		
65	Lock	E3-G033 / E6-2115 / E6-3112	Fits Noble wedge lock slot on Dell laptops Resettable 4-wheel number code Carbon steel cable	Fits Noble wedge lock slot on Dell laptops Resettable 4-wheel number code	Kensington N17 Dell Cable Lock for Laptops with Wedge Lock Slot	8		
					<b>Total MOP</b>		-	-

1 或同級或以上

2 有關項目之單價須包括送貨至澳門大學指定地點之運費及清關費等一切相關費用（即上述等費用不應作獨立項目報價，而一切相關費用須包括於單價中），競投者亦須密切留意有關進出口之法律及規定，以確保能運送到大學指定地點。此外，除獲列給之項目金額外，本大學不會支付任何額外費用。

3 大學祇接受競投者為「報價單」中每一單一項目提出最多壹個建議方案，多於壹個方案者，則僅對最高價格的壹個建議方案進行評審。

4 澳門大學可以按需要，持有保留部分項目判給的權利。

